



AUTOTEK

EVOLUTION OF POWER



CAR AUDIO RELOADED





street machine



A2150 2-CHANNEL

- 2 x 75 Watts RMS into 4 Ohms
- 2 x 125 Watts RMS into 2 Ohms
- 2 x 150 Watts Max. into 4 Ohms
- 2 x 250 Watts Max. into 2 Ohms
- Highlevel Inputs
- RCA In- and Outputs
- Highpassfilter 60 - 1200 Hz
- Lowpassfilter 40 - 150 Hz
- Bass Boost 0 - 12 db
- Mono bridgeable
- Illuminated Logo-Badge
- Dimensions: 255 x 55 x 220/280 mm

- 2 x 75 Watt RMS an 4 Ohm
- 2 x 125 Watt RMS an 2 Ohm
- 2 x 150 Watt Max. an 4 Ohm
- 2 x 250 Watt Max. an 2 Ohm
- Hochpegeleingänge
- Cinch Ein- und Ausgänge
- Hochpassfilter 60 - 1200 Hz
- Tiefpassfilter 40 - 150 Hz
- Bass-Anhebung 0 - 12 dB
- Mono brückbar
- Beleuchtetes Logo-Badge
- Abmessungen: 255 x 55 x 220/280 mm



A4150 4-CHANNEL

- 4 x 75 Watts RMS into 4 Ohms
- 4 x 125 Watts RMS into 2 Ohms
- 4 x 150 Watts Max. into 4 Ohms
- 4 x 250 Watts Max. into 2 Ohm
- Highlevel Inputs
- RCA In- and Outputs
- Highpassfilter 60 - 1200 Hz
- Lowpassfilter 30 - 250 Hz
- Bass Boost 0 - 12 db
- Mono bridgeable
- Illuminated Logo-Badge
- Dimensions: 255 x 55 x 280/340 mm

- 4 x 75 Watt RMS an 4 Ohm
- 4 x 125 Watt RMS an 2 Ohm
- 4 x 150 Watt Max. an 4 Ohm
- 4 x 250 Watt Max. an 2 Ohm
- Hochpegeleingänge
- Cinch Ein- und Ausgänge
- Hochpassfilter 60 - 1200 Hz
- Tiefpassfilter 30 - 250 Hz
- Bass-Anhebung 0 - 12 dB
- Mono brückbar
- Beleuchtetes Logo-Badge
- Abmessungen: 255 x 55 x 280/340 mm

AMPLIFIERS



RS5800 5-CHANNEL

- 4 x 75 + 1 x 200 Watts RMS into 4 Ohms
 - 4 x 125 + 1 x 300 Watts RMS into 2 Ohms
 - 4 x 150 + 1 x 400 Watts Max. into 4 Ohms
 - 4 x 250 + 1 x 600 Watts Max. into 2 Ohm
 - RCA Inputs
 - 2 x Highpassfilter 10 - 150 Hz (CH 1/2 + 3/4)
 - Lowpassfilter 30 - 150 Hz (CH5)
 - Bass Boost 0 - 12 dB (CH 5)
 - Subsonicfilter 15 - 55 Hz (CH 5)
 - Bass Remote Controller
 - Illuminated Logo-Badge
 - Dimensions: 255 x 55 x 500/560 mm
-
- 4 x 75 + 1 x 200 Watt RMS an 4 Ohm
 - 4 x 125 + 1 x 300 Watt RMS an 2 Ohm
 - 4 x 150 + 1 x 400 Watt Max. an 4 Ohm
 - 4 x 250 + 1 x 600 Watt Max. an 2 Ohm
 - Cinch Eingänge
 - 2 x Hochpassfilter 10 - 150 Hz (CH5)
 - Tiefpassfilter 30 - 150 Hz (CH5)
 - Bass-Anhebung 0 - 12 dB (CH 5)
 - Subsonicfilter 15 - 55 Hz (CH 5)
 - Bassfernbedienung
 - Beleuchtetes Logo-Badge
 - Abmessungen: 255 x 55 x 500/560 mm



MONOBLOCK
with LP-BP / Full / HP
Operation-Mode

R1400 MONOBLOCK

- 1 x 200 Watts RMS into 4 Ohms
 - 1 x 400 Watts RMS into 2 Ohms
 - 1 x 400 Watts Max. into 4 Ohms
 - 1 x 800 Watts Max. into 2 Ohms
 - RCA In- and Outputs
 - Lowpassfilter 40 - 150 Hz
 - Highpassfilter 80 - 2000 Hz
 - Subsonicfilter 15 - 55 Hz
 - Operation-Mode: LP-BP / Full / HP
 - Bass Boost 0 - 12 dB
 - Bass Remote Controller
 - Illuminated Logo-Badge
 - Dimensions: 255 x 55 x 250/310 mm
-
- 1 x 200 Watt RMS an 4 Ohm
 - 1 x 400 Watt RMS an 2 Ohm
 - 1 x 400 Watt Max. an 4 Ohm
 - 1 x 800 Watt Max. an 4 Ohm
 - Cinch Ein- und Ausgänge
 - Tiefpassfilter 40 - 150 Hz
 - Hochpassfilter 80 - 2000 Hz
 - Subsonicfilter 15 - 55 Hz
 - Betriebsmodis: LP-BP / Full / HP
 - Bass-Anhebung 0 - 12 dB
 - Bassfernbedienung
 - Beleuchtetes Logo-Badge
 - Abmessungen: 255 x 55 x 250/310 mm





SUPER SPORT



SS75.2 2-CHANNEL

- 2 x 75 Watts RMS into 4 Ohms
- 2 x 100 Watts RMS into 2 Ohms
- 2 x 150 Watts Max. into 4 Ohms
- 2 x 200 Watts Max. into 2 Ohms
- Highlevel Inputs
- RCA In- and Outputs
- Highpassfilter 10 - 1200 Hz
- Lowpassfilter 30 - 150 Hz
- Bass Boost 0 - 18 db
- Mono/Stereo Switch, Bandpass Mode
- Illuminated Logo-Badge
- Dimensions: 250 x 57 x 202/232 mm

- 2 x 75 Watt RMS an 4 Ohm
- 2 x 100 Watt RMS an 2 Ohm
- 2 x 150 Watt Max. an 4 Ohm
- 2 x 200 Watt Max. an 2 Ohm
- Hochpegeleingänge
- Cinch Ein- und Ausgänge
- Hochpassfilter 10 - 1200 Hz
- Tiefpassfilter 30 - 150 Hz
- Bass-Anhebung 0 - 18dB
- Mono/Stereo Schalter, Bandpass-Modus
- Beleuchtetes Logo-Badge
- Abmessungen: 250 x 57 x 202/232 mm



SS125.2 2-CHANNEL

- 2 x 125 Watts RMS into 4 Ohms
- 2 x 175 Watts RMS into 2 Ohms
- 2 x 250 Watts Max. into 4 Ohms
- 2 x 350 Watts Max. into 2 Ohms
- Highlevel Inputs
- RCA In- and Outputs
- Highpassfilter 10 - 1200 Hz
- Lowpassfilter 30 - 150 Hz
- Bass Boost 0 - 18 db
- Mono/Stereo Switch, Bandpass Mode
- Illuminated Logo-Badge
- Dimensions: 250 x 57 x 323/353 mm

- 2 x 125 Watt RMS an 4 Ohm
- 2 x 175 Watt RMS an 2 Ohm
- 2 x 250 Watt Max. an 4 Ohm
- 2 x 350 Watt Max. an 2 Ohm
- Hochpegeleingänge
- Cinch Ein- und Ausgänge
- Hochpassfilter 10 - 1200 Hz
- Tiefpassfilter 30 - 150 Hz
- Bass-Anhebung 0 - 18dB
- Mono/Stereo Schalter, Bandpass-Modus
- Beleuchtetes Logo-Badge
- Abmessungen: 250 x 57 x 323/353 mm



SS75.4 4-CHANNEL

- 4 x 75 Watts RMS into 4 Ohms
- 4 x 100 Watts RMS into 2 Ohms
- 4 x 150 Watts Max. into 4 Ohms
- 4 x 200 Watts Max. into 2 Ohms
- Highlevel Inputs
- RCA In- and Outputs
- Highpassfilter 10 - 1200 Hz
- Lowpassfilter 30 - 150 Hz
- Bass Boost 0 - 18 db
- Mono/Stereo Switch, Bandpass Mode
- Illuminated Logo-Badge
- Dimensions: 250 x 57 x 283/313 mm

- 4 x 75 Watt RMS an 4 Ohm
- 4 x 100 Watt RMS an 2 Ohm
- 4 x 150 Watt Max. an 4 Ohm
- 4 x 200 Watt Max. an 2 Ohm
- Hochpegeleingänge
- Cinch Ein- und Ausgänge
- Hochpassfilter 10 - 1200 Hz
- Tiefpassfilter 30 - 150 Hz
- Bass-Anhebung 0 - 18dB
- Mono/Stereo Schalter, Bandpass-Modus
- Beleuchtetes Logo-Badge
- Abmessungen: 250 x 57 x 283/313 mm

AMPLIFIERS



SS100.4 4-CHANNEL

- 4 x 100 Watts RMS into 4 Ohms
 - 4 x 150 Watts RMS into 2 Ohms
 - 4 x 200 Watts Max. into 4 Ohms
 - 4 x 300 Watts Max. into 2 Ohms
 - Highlevel Inputs
 - RCA In- and Outputs
 - Highpassfilter 10 - 1200 Hz
 - Lowpassfilter 30 - 150 Hz
 - Bass Boost 0 - 18 dB
 - Mono/Stereo Switch, Bandpass Mode
 - Illuminated Logo-Badge
 - Dimensions: 250 x 57 x 364/394 mm
-
- 4 x 100 Watt RMS an 4 Ohm
 - 4 x 150 Watt RMS an 2 Ohm
 - 4 x 200 Watt Max. an 4 Ohm
 - 4 x 300 Watt Max. an 2 Ohm
 - Hochpegeleingänge
 - Cinch Ein- und Ausgänge
 - Hochpassfilter 10 - 1200 Hz
 - Tiefpassfilter 30 - 150 Hz
 - Bass-Anhebung 0 - 18dB
 - Mono/Stereo Schalter, Bandpass-Modus
 - Beleuchtetes Logo-Badge
 - Abmessungen: 250 x 57 x 364/394 mm



SS750.1 MONOBLOCK

- 1 x 325 Watts RMS into 4 Ohms
 - 1 x 500 Watts RMS into 2 Ohms
 - 1 x 750 Watts RMS into 1 Ohms
 - 1 x 650 Watts RMS into 4 Ohms
 - 1 x 1000 Watts Max. into 2 Ohms
 - 1 x 1500 Watts Max. into 1 Ohms
 - RCA In- and Outputs
 - Lowpassfilter 30 - 150 Hz
 - Subsonicfilter 15 - 55 Hz
 - Bass Boost 0 - 12 dB
 - Bass Remote Controller
 - Illuminated Logo-Badge
 - Dimensions: 250 x 57 x 453/483 mm
-
- 1 x 325 Watt RMS an 4 Ohm
 - 1 x 500 Watt RMS an 2 Ohm
 - 1 x 750 Watt RMS an 1 Ohm
 - 1 x 650 Watt RMS an 4 Ohm
 - 1 x 1000 Watt Max. an 2 Ohm
 - 1 x 1500 Watt Max. an 1 Ohm
 - Cinch Ein- und Ausgänge
 - Tiefpassfilter 30 - 150 Hz
 - Subsonicfilter 15 - 55 Hz
 - Bass-Anhebung 0 - 12 dB
 - Bassfernbedienung
 - Beleuchtetes Logo-Badge
 - Abmessungen: 250 x 57 x 453/483 mm





street machine



A300RX BASSREFLEX SUBBOX

- 12" (30 cm) Subwoofer with 2" (50 mm) Voice Coil
- 400 Watts RMS, 800 Watts Max., Impedance 4 Ohms
- Chrome plated Protection Bars, Logo-Embroidery
- Dimensions: 470 x 370 x 470/250 mm
- 12" (30 cm) Subwoofer mit 2" (50 mm) Schwingspule
- 400 Watt RMS, 800 Watt Max., Impedanz 4 Ohm
- Verchromte Schutzbügel, Logostick
- Abmessungen: 470 x 370 x 470/250 mm

A250RX BASSREFLEX SUBBOX

- 10" (25 cm) Subwoofer with 2" (50 mm) Voice Coil
- 250 Watts RMS, 500 Watts Max., Impedance 4 Ohms
- Chrome plated Protection Bars, Logo-Embroidery
- Dimensions: 325 x 335 x 400/300 mm
- 10" (25 cm) Subwoofer mit 2" (50 mm) Schwingspule
- 250 Watt RMS, 500 Watt Max., Impedanz 4 Ohm
- Verchromte Schutzbügel, Logostick
- Abmessungen: 325 x 335 x 400/300 mm



A300BP BANDPASS SUBBOX

- 12" (30 cm) Subwoofer with 2" (50 mm) Voice Coil
- 400 Watts RMS, 800 Watts Max., Impedance 4 Ohms
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 500 x 380 x 500/300 mm
- 12" (30 cm) Subwoofer mit 2" (50 mm) Schwingspule
- 400 Watt RMS, 800 Watt Max., Impedanz 4 Ohm
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 500 x 380 x 500/300 mm

subboxes



A700BP DUAL BANDPASS SUBBOX

- 2 x 12" (30 cm) Subwoofer with 2" (50 mm) Voice Coil
- 700 Watts RMS, 1400 Watts Max., Impedance 4 Ohms
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 780 x 380 x 450/360 mm

- 2 x 12" (30 cm) Subwoofer mit 2" (50 mm) Schwingspule
- 700 Watt RMS, 1400 Watt Max., Impedanz 4 Ohm
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 780 x 380 x 450/360 mm

A350BP BANDPASS SUBBOX

- 12" (30 cm) Subwoofer with 2" (50 mm) Voice Coil
- 350 Watts RMS, 700 Watts Max., Impedance 4 Ohms
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 405 x 380 x 450/360 mm

- 12" (30 cm) Subwoofer mit 2" (50 mm) Schwingspule
- 350 Watt RMS, 700 Watt Max., Impedanz 4 Ohm
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 405 x 380 x 450/360 mm



A250BP BANDPASS SUBBOX

- 10" (25 cm) Subwoofer with 2" (50 mm) Voice Coil
- 250 Watts RMS, 500 Watts Max., Impedance 4 Ohms
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 405 x 340 x 390/310 mm

- 10" (25 cm) Subwoofer mit 2" (50 mm) Schwingspule
- 250 Watt RMS, 500 Watt Max., Impedanz 4 Ohm
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 405 x 340 x 390/310 mm





street machine



A6.2CS COMPONENT-SYSTEM

- 6,5" (16,5 cm) 2-Way-Component-System
- 100 Watts RMS, 200 Watts Max., Impedance 4 Ohms
- Inline-Crossover, 20 mm Neodymium-Tweeter
- Frequency Response 50 Hz - 20 KHz
- Mounting Depth 57 mm, Mounting Hole 143 mm
- 6,5" (16,5 cm) 2-Wege-Komponenten-System
- 100 Watt RMS, 200 Watt Max., Impedanz 4 Ohm
- Inline-Kabel-Frequenzweiche, 20 mm Neodym-Hochtöner
- Frequenzgang 50 Hz - 20 KHz
- Einbautiefe 57 mm, Einbauöffnung 143 mm

A693TX TRIAX-SYSTEM

- 6 x 9" 3-Way-Triax-System
- 150 Watts RMS, 300 Watts Max., Impedance 4 Ohms
- Frequency Response 40 Hz - 20 KHz
- Mounting Depth 81 mm, Mounting Hole 151 x 220 mm
- 6 x 9" 3-Wege-Triax-System
- 150 Watt RMS, 300 Watt Max., Impedanz 4 Ohm
- Frequenzgang 40 Hz - 20 KHz
- Einbautiefe 81 mm, Einbauöffnung 151 x 220 mm



SPEAKERS



A62CX COAX-SYSTEM

- 6.5" (16.5 cm) 2-Way-Coax-System
- 100 Watts RMS, 200 Watts Max. Impedance 4 Ohms
- Frequency Response 50 Hz - 20 KHz
- Mounting Depth 57 mm, Mounting Hole 143 mm
- 6.5" (16.5 cm) 2-Wege-Koax-System
- 100 Watt RMS, 200 Watt Max. Impedanz 4 Ohm
- Frequenzgang 50 Hz - 20 KHz
- Einbautiefe 57 mm, Einbauöffnung 143 mm

A52CX COAX-SYSTEM

- 5.25" (13 cm) 2-Way-Coax-System
- 80 Watts RMS, 160 Watts Max., Impedance 4 Ohms
- Frequency Response 65 Hz - 20 KHz
- Mounting Depth 55 mm, Mounting Hole 116 mm
- 5.25" (13 cm) 2-Wege-Koax-System
- 80 Watt RMS, 160 Watt Max., Impedanz 4 Ohm
- Frequenzgang 65 Hz - 20 KHz
- Einbautiefe 55 mm, Einbauöffnung 116 mm



A42CX COAX-SYSTEM

- 4" (10 cm) 2-Way-Coax-System
- 60 Watts RMS, 120 Watts Max., Impedance 4 Ohms
- Frequency Response 80 Hz - 20 KHz
- Mounting Depth 48 mm, Mounting Hole 94 mm
- 4" (10 cm) 2-Wege-Koax-System
- 60 Watt RMS, 120 Watt Max., Impedanz 4 Ohm
- Frequenzgang 80 Hz - 20 KHz
- Einbautiefe 48 mm, Einbauöffnung 94 mm





AT 10 KIT AMPLIFIER WIREKIT

- 1 x 10 mm² Power Wire (red), 5 m
- 1 x 10 mm² Ground Wire (grey), 0,8 m
- 1 x RCA Stereo Audio Cable (blue), double shielded, 5 m
- 1 x 0,5 mm² Remote Wire, 5 m
- 1 x AGU Fuseholder with 40 A Fuse

- 1 x 10 mm² Stromkabel (rot), 5 m
- 1 x 10 mm² Massekabel (grau), 0,8 m
- 1 x Cinch Stereo Audio Kabel (blau), doppelt abgeschirmt, 5 m
- 1 x 0,5 mm² Steuerleitung, 5 m
- 1 x AGU Sicherungshalter mit 40 A Sicherung



AT 20 KIT AMPLIFIER WIREKIT

- 1 x 20 mm² Power Wire (red), 5 m
- 1 x 20 mm² Ground Wire (grey), 0,8 m
- 1 x RCA Stereo Audio Cable (blue), double shielded, 5 m
- 1 x 0,5 mm² Remote Wire, 5 m
- 1 x AGU Fuseholder with 60 A Fuse

- 1 x 20 mm² Stromkabel (rot), 5 m
- 1 x 20 mm² Massekabel (grau), 0,8 m
- 1 x Cinch Stereo Audio Kabel (blau), doppelt abgeschirmt, 5 m
- 1 x 0,5 mm² Steuerleitung, 5 m
- 1 x AGU Sicherungshalter mit 60 A Sicherung



accessories



AT 1200 CAP

- Power Capacitor 1,2 Farad Capacity
- 3-digit Voltmeter-Display, solid Acrylic Brackets
- Dimensions: 125 x 76 x 260 mm

- Pufferelko 1,2 Farad Kapazität
- 3-stellige Spannungs-Anzeige, stabile Acryl-Halterungen
- Abmessungen: 125 x 76 x 260 mm



AUTOTEK GEAR

T-SHIRTS

- Logo-Print front and back, 215 g/m², 100 % Cotton
- Logo-Druck vorne und hinten, 215 g/m², 100 % Baumwolle
- AT-110-B royal blue / royal blau L / XL / XXL
- AT-110-NY navy blue / marine blau L / XL / XXL
- AT-110-S black / schwarz L / XL / XXL

BASEBALL SHIRTS

- Logo-Print front, 165 g/m², 85 % Cotton
- Logo-Druck vorne, 165 g/m², 85 % Baumwolle
- AT-120-AW ash-white / grau-weiß L / XL / XXL
- AT-120-NW navy-white / marine-weiß L / XL / XXL

BASEBALL LONG SLEEVE SHIRTS

- Logo-Print front, 165 g/m², 85 % Cotton
- Logo-Druck vorne, 165 g/m², 85 % Baumwolle
- AT-130-AW ash-white / grau-weiß L / XL / XXL
- AT-130-NW navy-white / marine-weiß L / XL / XXL



AUTOTEK

EVOLUTION OF POWER



DISTRIBUTION: Audio Design GmbH · Am Breillingsweg 3 · D-76709 Kronau
Tel. +49 (0)7253 - 9465-0 · Fax +49 (0)7253 - 946510 · www.audiodesign.de

© Audio Design GmbH, all rights reserved